

MATERIAL SAFETY DATA SHEET

AUSTIN POWER PLYWOOD

WOOD VENEER PRODUCT

IMPORTANT NOTICE:

This Material Safety Data Sheet (MSDS) is written by International Panels (Australia) Pty Ltd 17 Babb Doyle Street, LOGANHOLME, QLD 4129 (07) 3875 1826 in accordance with work safe Australia Guidelines. As such, the company information contained herein must not be altered, deleted or added to, International Panels (Australia) Pty Ltd will issue a new MSDS when there is a change in product specifications and/or Work safe Australia guidelines/regulations.

International Panels (Australia) Pty Ltd will not accept responsibility for any changes made to its MSDS in content by any person.

IDENTIFICATION

Product Name: Austin Power Plywood
Includes: 5.5mm "A" Bonded Bendi Plywood
Manufacturer: B.S Progressive Pvt Ltd
3A Pollock Street, Kolkata, India 700001

UN Number: Not Allocated
Registered Trade Name: Austin Power Plywood
Dangerous Goods Class: None Allocated
Hazchem Code: None Allocated
Poisons Schedule: None Allocated
Use: Residential, Commercial, Industrial and Marine Construction, furniture and fitments and/or general purpose building material.

PHYSICAL DESCRIPTION/PROPERTIES

Appearance:

The product is manufactured as pressed boards at a standard thickness from 5.5mm. They are made from wood veneer of a range of species which are bonded together with resin. "Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation.

Users are advised to make their own determination as to the suitability of this information in relation to their particular purpose and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of the information.

ODOUR:

No distinctive odour. Newly manufactured plywood and freshly machined surfaces tend to have the odour of the wood species from which the plywood was manufactured.

Boiling Point: Not Applicable
Vapour Density : Not Applicable
Melting Point: Not Applicable
Solubility in Water: Not Applicable
Flash Point: Not Applicable
Specific Gravity: 0.50 – 1.00
Flammability in Air: Fine airborne dust generated when the product is machined, can ignite spontaneously.



INGREDIENTS:

| Substances/Chemical Entity | CAS No. | Properties by Weight |
|----------------------------|------------|----------------------|
| Wood Veneer | None | >92 % |
| Phenol Formaldehyde | 40798-65-0 | < 8% |

HEALTH HAZARD INFORMATION:

Health Effects: Plywood is not classified as hazardous according to criteria of Worksafe Australia.

WARNING:

DO NOT BREATH WOOD DUST: AVOID CONTACT WITH EYES, OR

AVOID BREATHING WOOD DUST: AVOID CONTACT EYES

(2) PACKING WARNING LABEL:

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions.

The provision of this information should not be construed as a recommendation to use any products in violation of any patent rights or in breach of any statute or regulation.

Users are advised to make their own determination as to the suitability of this information in relation to their particular purpose and specific circumstances.

Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of the information.

WARNING

Wood dust produced by machining or sanding wood products including plywood, may cause irritation to the eyes, nose and throat.

It may also cause sensitisation, e.g. dermatitis and asthma

Repeated and prolonged exposure to wood dust may cause nasal cancer.

AVOID BREATHING WOOD DUST: AVOID CONTACT WITH EYES

Work in a clean, well ventilated area with machines that are equipped with efficient dust extraction systems, or if these are not available wear an Australian/New Zealand standards approved dust mask and eye protection. Respirators/dust masks should comply with AS/NZS 1716 and be selected and maintained in accordance with AS/NZS 1337, should be worn when machining these products.

Further information in regard to the safe use and handling of these products is available from:

International Panels (Australia) Pty Ltd

17 Babb Doyle Street,

LOGANHOLME QLD 4129

Phone: (07) 3875 1826 Fax No: (07) 3209 9159

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions.

The provision of this information should not be construed as a recommendation to use any products in violation of any patent rights or in breach of any statute or regulation.

Users are advised to make their own determination as to the suitability of this information in relation to their particular purpose and specific circumstances.

Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of the information.

